





E600 TRAFFIC AREAS SUBJECT TO **HIGH WHEEL LOADS**



All our documents can be downloaded free of charge from: www.nicoll.fr

New range of drainage channels Kenadrain® E600

Environment

NEW





The new range of drainage channels Kenadrain® is designed for areas subject to significant axle loads (E600 load rating) enabling use of the width from 100 to 300.

Advantages:

- Robust : complies with NF EN 1433
- Efficient: excellent hydraulic capacity
- Practical: interlocked, supplied already fitted to the drainage channel
- Safe: complies with accessibility requirements for people with reduced mobility, high mechanical strength, slip-resistant
- Durable: resistant to the main chemical agents
- Aesthetic and functional : an innovative design in a black matt colour







ENVIRONMENT

HYDRAULIC DRAINAGE CHANNELS - E600

Kenadrain®	HD -	Width	100 int.
\smile			

	DESCRIPTION	REF.	Packing	Packaging
	DUCTILE IRON GRATING			
STATE OF THE PARTY	Channel length 1 m with galvanized steel edges and 2 ductile iron gratings Height 2 - 170 mm	32 DR102EF		Delivered pe
	Locking: 1 screw per grating on galvanized locking bar	132		and sold pe elements of 1 m
	Pallet of 40 m (Delivery unit)	PFR102EF		
	Channels classed E600 are available in fumigated pallets only.		<u>'</u>	
	ACCESSORIES			
	End cap/end outlet			
	Height 0 - Ø 50	NJDR100		10
	Height 1 - Ø 75	NPDR101		10
5	Height 2 - Ø 100	NTDR102		10
	Height 2 - Ø 110	NVDR102		10
	Height 3 - Ø 100	NTDR103		10
	Height 3 - Ø 110	NVDR103		10
	Height 4 - Ø 100	NTDR104		10
	Height 4 - Ø 110	NVDR104		10
	Lateral/vertical outlet (delivered with screws)			
	Lateral or vertical Ø 100	STDR10		10
in .	Lateral or vertical Ø 110	SVDR10		10
	Lateral or vertical Ø 125	SXDR10		10
	Lateral or vertical Ø 160	SZDR20		10
	Step connector	SAB10		
-	Adaptation part for sump PS100X, PS100V, STDR10, SVDR10 and SXDR10 for depths 3 and 4 of stepped-fall range	ADPS100		
	SECURITY LOCKING SYSTEM			
0	Set of 24 security bolts	VISDRI	S1	
a	0 11 111		0.1	
8	Security lock key	CLEDRI	S1	
	SUMP			
1041	Ekso sump with lower outlet			
70	width 100 - outlet Ø 125	PS100X		4
	width 100 - outlet Ø 110	PS100V		4
	Ekso sump with upper outlet			
	width 100 - outlet Ø 125	PS100XH		
·	width 100 - outlet Ø 110	PS100VH		

HYDRAULIC DRAINAGE CHANNELS - E600

Kenadrain® HD - Width 150 int. DESCRIPTION **DRAWINGS** REF. Packing Packaging **DUCTILE IRON GRATING** Channel length 1 m with galvanized steel edges Delivered per and 2 ductile iron gratings DR152EF pallet of 30 m and Locking: 4 screws per grating sold per elements of 1 m Pallet of 30 m (Delivery unit) PFR152EF Channels classed E600 are available in fumigated pallets only. **ACCESSORIES** End cap/end outlet Ø 125 NXDR152 10 Lateral/vertical outletl (delivered with screws) Lateral Ø 125 10 SXDR10 Vertical Ø 160 10 SZDR20 **SECURITY LOCKING SYSTEM** Set of 24 security bolts **VISDRI** Security lock key S1 **CLEDRI SUMP** Ekso sump with lower outlet width 150 - outlet Ø 160 2 PS150Z Ekso sump with upper outlet width 150 - outlet Ø 160 PS150ZH

NEW!

SAUL

ENVIRONMENT

	DESCRIPTION	DRAWINGS	REF.	Packing	Packaging
	DUCTILE IRON GRATING				
	Channel length 1 m with galvanized steel edges	20 242 42			
VIII.	and 2 ductile iron gratings Locking: 4 screws per grating	† ₁	DR202EF		Delivered per pallet of 20 n
AND THE PERSON NAMED IN	Locking. 4 dorows per graining	- 202 - 00 N			and sold per elements of 1
	Pallet of 20 m (Delivery unit)	249	PFR202EF		
All Marie					
•					
	Channels classed E600 are available in fumigated pallets	only.			
	ACCESSORIES				
	End cap/end outlet				
	Ø 160		NZDR202		10
	Lateral/vertical outlet (delivered with screws)				
	Lateral Ø 160		SZDR20		10
	Vertical Ø 200		SBDR20		10
	SECURITY LOCKING SYSTEM				
00					
0	Set of 24 security bolts		VISDRI	S1	
CK	Security lock key		OI EDDI	S1	
	Security lock key		CLEDRI	31	
	SUMP				
12.					
101	Ekso sump with lower outlet				
	width 200 - outlet Ø 200		PS200B		2
	Ekso sump with upper outlet				
	width 200 - outlet Ø 200		PS200BH		
	WIGHT ZOO OUHOL & ZOO		r SZUUDII		

HYDRAULIC DRAINAGE CHANNELS

		DESCRIPTION	DRAWINGS	REF.	Packing	Packaging
		DUCTILE IRON GRATING				
		Channel length 1 m with galvanized steel edges and 2 ductile iron gratings Locking: 4 screws per grating	20 1 64 64	DR302EF		Delivered per pallet of 9 m and sold per elements
	11.00	Pallet of 9 m (Delivery unit)	361	PFR302EF		of 1 m
		Channels classed E600 are available in fumigated palle	ts only.			
		ACCESSORIES				
		Find and found available				
		End cap/end outlet Ø 250		NDDR302		
		Lateral/vertical outlet (delivered with screws)				
	JU	Lateral Ø 200 Vertical Ø 315		SBDR20 SEDR30		10
		SECURITY LOCKING SYSTE	M			
6	NO.					
	0	Set of 24 security bolts		VISDRI	S1	
	4	Security lock key		CLEDRI	S1	
		SUMP				
	\geq					
-		Ekso sump with lower outlet width 300 - outlet Ø 315		PS300E		
		Ekso sump with upper outlet				
1		width 300 - outlet Ø 315		PS300EH		