

# PARABOND®

CEMENTS / PRIMERS / CLEANERS  
FOR PVC / CPVC / ABS



PRODUCT  
REFERENCE  
CATALOG

“Engineered for Plastic Piping Systems”

# CEMENTS / PRIMERS / CLEA

## P-8 PVC Solvent Cement Regular Bodied - Clear



A regular bodied, fast setting, high strength PVC solvent cement designed for joining PVC Schedule 40 pressure pipe and fittings through 4" diameter, non-pressure through 6" diameter. Non-pressure applications include conduit, sewer, and drain, waste and vent (DWV) systems. When used for pressure applications or pipe and fittings 5" diameter or larger, use of Parabond® C-60 primer prior to cementing is recommended.

Temperature application range is 40° - 110° F.  
3 Year Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P0080	01006	24
1/2 pint w/dauber (.237 ml)	P0081	02006	24
1 pint w/dauber (.473 ml)	P0082	04006	12
1 quart w/dauber (.946 ml)	P0083	07010	12
1 gallon "F" style (3.785L)	P0084	08011	6



Meets  
ASTM  
D-2564



## P-10 PVC Solvent Cement Medium Bodied - Clear



A medium bodied, fast setting, high strength PVC solvent cement designed for joining PVC Schedule 40 pressure pipe and fittings through 6" diameter, and up to 2" diameter on Schedule 80. Applications include potable water, conduit, sewer, and drain, waste and vent (DWV) systems. When used for pressure applications, pipe and fittings 5" or larger and on Schedule 80 systems, use of Parabond® C-60 primer prior to cementing is recommended.

Temperature application range is 40° - 110° F.  
3 Year Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P0100	01007	24
1/2 pint w/dauber (.237 ml)	P0101	02007	24
1 pint w/dauber (.473 ml)	P0102	04007	12
1 quart w/dauber (.946 ml)	P0103	07011	12
1 gallon "F" style (3.785 L)	P0104	08012	6



Meets  
ASTM  
D-2564



## P-14 PVC Solvent Cement Heavy Bodied - Gray



A specially formulated heavy bodied, medium setting, high strength PVC solvent cement designed for joining larger pipe sizes. For use on Schedule 40 and Schedule 80 pressure pipe and fittings through 12" diameter. Applications include potable water, conduit, sewer, and drain, waste and vent (DWV) systems. When used for pressure applications, pipe and fittings 5" diameter or larger and Schedule 80 systems, use of Parabond® C-60 primer prior to cementing is recommended.

Temperature application range is 40° - 110° F.  
3 Year Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P1401	01012	24
1/2 pint w/dauber (.237 ml)	P1411	02012	24
1 pint w/dauber (.473 ml)	P1421	04012	12
1 quart w/dauber (.946 ml)	P1431	07016	12
1 gallon "F" style (3.785 L)	P1441	08016	6



Meets  
ASTM  
D-2564



## P-14 PVC Solvent Cement Heavy Bodied - Clear



A specially formulated heavy bodied, medium setting, high strength PVC solvent cement designed for joining larger pipe sizes. For use on Schedule 40 and Schedule 80 pressure pipe and fittings through 12" diameter. Applications include potable water, conduit, sewer, and drain, waste and vent (DWV) systems. When used for pressure applications, pipe and fittings 5" diameter or larger and Schedule 80 systems, use of Parabond® C-60 primer prior to cementing is recommended.

Temperature application range is 40° - 110° F.  
3 Year Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P0140	01011	24
1/2 pint w/dauber (.237 ml)	P0141	02011	24
1 pint w/dauber (.473 ml)	P0142	04011	12
1 quart w/dauber (.946 ml)	P0143	07015	12
1 gallon "F" style (3.785 L)	P0144	08015	6



Meets  
ASTM  
D-2564



## P-600 PVC Solvent Cement Regular Bodied - Clear



A regular bodied, fast setting, high strength PVC solvent cement formulated for joining PVC Schedule 40 pressure pipe and fittings through 4" diameter, non-pressure through 6" diameter. Non-pressure applications include conduit, sewer, and drain, waste and vent (DWV) systems. When used for pressure applications or pipe and fittings 5" diameter or larger, use of Parabond® C-60 primer prior to cementing is recommended.

Temperature application range is 40° - 110° F.  
3 Year Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P6000	01021	24
1/2 pint w/dauber (.237 ml)	P6001	02021	24
1 pint w/dauber (.473 ml)	P6002	04022	12
1 quart w/dauber (.946 ml)	P6003	07027	12
1 gallon "F" style (3.785 L)	P6004	08026	6



Meets  
ASTM  
D-2564

## P-30 PVC All Climate Solvent Cement Regular Bodied - Blue



A regular bodied, extremely fast setting, high strength PVC solvent cement specifically designed to meet fast setting pressure application requirements. Suitable for use on pipe and fittings where moisture or wet conditions exist. Recommended for Schedule 40 pressure pipe and fittings through 4" diameter, non-pressure applications through 6" diameter. Non-pressure applications include conduit, sewer, and drain, waste and vent (DWV) systems. When used for pressure applications or pipe and fittings 5" diameter or larger, use of Parabond® C-60 primer prior to cementing is recommended. Temperature application range is 0° - 110° F.

3 Year Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P0300	01018	24
1/2 pint w/dauber (.237 ml)	P0301	02018	24
1 pint w/dauber (.473 ml)	P0302	04019	12
1 quart w/dauber (.946 ml)	P0303	07024	12
1 gallon "F" style (3.785 L)	P0304	08023	6



Meets  
ASTM  
D-2564

# PRIMER FOR PVC / CPVC / ABS

## P-18 CPVC Solvent Cement Regular Bodied - Orange



A regular bodied fast setting, high strength CPVC solvent cement formulated for joining copper tube size and Schedule 40 pipe and fittings through 2" diameter interference fit. The use of Parabond® C-60 primer prior to cementing is recommended. CPVC pipe and fittings are specifically designed for cold and hot water systems up to 180° F. Temperature application range is 40° - 110° F. 2 Year Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P0180	01014	24
1/2 pint w/dauber (.237 ml)	P0181	02014	24
1 pint w/dauber (.473 ml)	P0182	04015	12
1 quart w/dauber (.946 ml)	P0183	07019	12



## P-19 CPVC CTS Solvent Cement Medium Bodied - Yellow



A medium bodied, fast setting, high strength CPVC solvent cement for copper tube size (CTS) pipe and fittings through 2" diameter interference fit only. CPVC pipe and fittings are specially designed for cold and hot water systems up to 180°F. Temperature application range is 40° - 110°F. Flowguard Gold® is a registered trademark of Noveon Inc. 2 Year Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P0190	01025	24
1/2 pint w/dauber (.237 ml)	P0191	02019	24
1 pint w/dauber (.473 ml)	P0192	04041	12
1 quart w/dauber (.946 ml)	P0193	07030	12



## P-20 CPVC Solvent Cement Heavy Bodied - Orange



A heavy bodied, medium setting, high strength CPVC solvent cement formulated for joining Schedule 40 and Schedule 80 pipe and fittings through 12" diameter. The use of Parabond® C-60 primer prior to cementing is recommended. CPVC pipe and fittings are specifically designed for cold and hot water systems up to 180° F. Temperature application range is 40° - 110° F. 2 Year Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P0200	01015	24
1/2 pint w/dauber (.237 ml)	P0201	02015	24
1 pint w/dauber (.473 ml)	P0202	04016	12
1 quart w/dauber (.946 ml)	P0203	07020	12



## P-28 Multi-Purpose Solvent Cement Regular Bodied - Clear



A regular bodied, fast setting, high strength, multi-purpose cement formulated for joining PVC and CPVC pressure pipe and fittings through 4" diameter. May also be used on ABS and other non-pressure systems through 6" diameter. Non-pressure applications include conduit, sewer and drain, waste and vent (DWV) systems. When used for pressure applications or pipe 5" diameter and larger, use of Parabond® C-60 primer on the PVC and/or CPVC pipe and fittings prior to cementing is recommended. This product offers the flexibility of one cement where several plastic types are used. Temperature application range is 40° - 110° F. 3 Year Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P0280	01016	24
1/2 pint w/dauber (.237 ml)	P0281	02016	24
1 pint w/dauber (.473 ml)	P0282	04018	12
1 quart w/dauber (.946 ml)	P0283	07023	12

## P-750 Pipe Joint Lubricant White



A non-toxic, water soluble, pipe lubricant designed for assembly of gasketed pipe. Adheres to wet or dry pipe. Temperature application range is 0° - 110°F.

Size	Old Stock Number	New Stock Number	Cans per Case
1 quart w/dauber (.946 ml)	P0750	07050	12
1 gallon "F" style (3.785 L)	P0751	08036	4

## C-70 PVC, CPVC and ABS Cleaner Clear



This cleaner is formulated to be used with Parabond PVC, CPVC and ABS solvent cement products. Cleaning the pipe and fitting prior to cementing always yields better results. The cleaner should be used to remove dirt, oil, grease and other foreign material from the surface of the pipe and fittings to be cemented. This will insure a clean joint enabling the installer to apply a uniform amount of cement for a strong, tight joint. Temperature application range is 0° - 110°F. Unlimited Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P0700	01005	24
1/2 pint w/dauber (.237 ml)	P0701	02005	24
1 pint w/dauber (.473 ml)	P0702	04005	12
1 quart w/dauber (.946 ml)	P0703	07009	12
1 gallon F style (3.785 L)	P0704	08010	6

**C-60 PVC and CPVC Primer  
Clear**



For surface preparation of PVC and CPVC pipe and fittings prior to cement application. The function of primer is to remove surface gloss and soften pipe and fitting surfaces which is necessary for the proper solvent welding of the materials.  
Temperature application range is 0° - 110° F.  
3 Year Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P0600	01001	24
1/2 pint w/dauber (.237 ml)	P0601	02001	24
1 pint w/dauber (.473 ml)	P0602	04001	12
1 quart w/dauber (.946 ml)	P0603	07005	12
1 gallon "F" style (3.785 L)	P0604	08006	6



Meets  
ASTM  
F-656

**C-60 PVC and CPVC Primer  
Purple**



For surface preparation of PVC and CPVC pipe and fittings prior to cement application. The function of primer is to remove surface gloss and soften pipe and fitting surfaces which is necessary for the proper solvent welding of the materials.  
Temperature application range is 0° - 110° F.  
3 Year Shelf Life

Size	Old Stock Number	New Stock Number	Cans per Case
1/4 pint w/dauber (.118 ml)	P0606	01002	24
1/2 pint w/dauber (.237 ml)	P0607	02002	24
1 pint w/dauber (.473 ml)	P0608	04002	12
1 quart w/dauber (.946 ml)	P0609	07006	12
1 gallon "F" style (3.785 L)	P0610	08007	6



Meets  
ASTM  
F-656



**Quality and Customers ////////////////**

**PARABOND®**

*is committed to conducting business with integrity and excellence. Our goal is continuous improvement of products and services. This goal will be achieved by recognizing and respecting the partnership we*

*have with our customers, suppliers, employees and the community.*

*Our customers are our first priority. We will provide them with consistently reliable and innovative products and services, based on mutually agreed upon standards and furnish the technical assistance needed to assure these products are used efficiently and safely.*

***If you have any questions, please feel free to contact us.***

**PARABOND® Export Department  
190 E. Washington Street  
P.O. Box 749  
Chagrin Falls, OH 44022 U.S.A.  
Phone: (440) 247-3570  
Fax: (440) 247-2132  
E-mail: marus@m-winc.com**

**PARABOND® is distributed by:**